

Inch Extended



Part Number	Ring Material	ID	OD	Width	Flange OD	Flange Width	Shield Type	Dynamic Load	Static Load	Limited Speed(x1K rpm)	System of Measurement	Bearing Type	Ball Bearing Type	Construction	Precision	Clearance	Temperature Range	RoHS	SGS
RW4zz	52100 Chrome Steel	0.25"	0.625"	0.196"	0.364"	0.2273"	Shielded	283 lbf	112 lbf	38	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SRW4	440C Stainless Steel	0.25"	0.625"	0.196"	0.364"	0.2273"	Open	255 lbf	101 lbf	34.2	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
RW4	52100 Chrome Steel	0.25"	0.625"	0.196"	0.364"	0.2273"	Open	283 lbf	112 lbf	38	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SRW188zz	440C Stainless Steel	0.25"	0.5"	0.1875"	0.33"	0.2188"	Shielded	186 lbf	72 lbf	36	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
RW168	52100 Chrome Steel	0.25"	0.375"	0.125"	0.285"	0.1562"	Open	71 lbf	31 lbf	48	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SRW168	440C Stainless Steel	0.25"	0.375"	0.125"	0.285"	0.1562"	Open	64 lbf	28 lbf	43.2	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
RW168zz	52100 Chrome Steel	0.25"	0.375"	0.125"	0.285"	0.1562"	Shielded	71 lbf	31 lbf	48	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SRW168zz	440C Stainless Steel	0.25"	0.375"	0.125"	0.285"	0.1562"	Shielded	64 lbf	28 lbf	43.2	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
RW188	52100 Chrome Steel	0.25"	0.5"	0.125"	0.33"	0.1562"	Open	207 lbf	80 lbf	40	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SRW188	440C Stainless Steel	0.25"	0.5"	0.125"	0.33"	0.1562"	Open	186 lbf	72 lbf	36	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SRW3	440C Stainless Steel	0.1875"	0.5"	0.1562"	0.276"	0.1875"	Open	224 lbf	79 lbf	38.7	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SRW3zz	440C Stainless Steel	0.1875"	0.5"	0.196"	0.276"	0.2273"	Shielded	224 lbf	79 lbf	38.7	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
RW3zz	52100 Chrome Steel	0.1875"	0.5"	0.196"	0.276"	0.2273"	Shielded	249 lbf	88 lbf	43	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
RW3	52100 Chrome Steel	0.1875"	0.5"	0.1562"	0.276"	0.1875"	Open	249 lbf	88 lbf	43	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SRW166zz	440C Stainless Steel	0.1875"	0.375"	0.125"	0.235"	0.1562"	Shielded	122 lbf	44 lbf	45	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
RW166zz	52100 Chrome Steel	0.1875"	0.375"	0.125"	0.235"	0.1562"	Shielded	136 lbf	49 lbf	50	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SRW166	440C Stainless Steel	0.1875"	0.375"	0.125"	0.235"	0.1562"	Open	122 lbf	44 lbf	45	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
RW166	52100 Chrome Steel	0.1875"	0.375"	0.125"	0.235"	0.1562"	Open	136 lbf	49 lbf	50	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SRW156zz	440C Stainless Steel	0.1875"	0.3125"	0.125"	0.221"	0.1562"	Shielded	62 lbf	24 lbf	47.7	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
RW156zz	52100 Chrome Steel	0.1875"	0.3125"	0.125"	0.221"	0.1562"	Shielded	69 lbf	27 lbf	53	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SRW156	440C Stainless Steel	0.1875"	0.3125"	0.1094"	0.221"	0.1406"	Open	62 lbf	24 lbf	47.7	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
RW156	52100 Chrome Steel	0.1875"	0.3125"	0.1094"	0.221"	0.1406"	Open	69 lbf	27 lbf	53	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SRW2-6zz	440C Stainless Steel	0.125"	0.375"	0.1406"	0.173"	0.1719"	Shielded	110 lbf	37 lbf	47.7	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SRW155zz	440C Stainless Steel	0.15625"	0.3125"	0.125"	0.221"	0.1562"	Shielded	62 lbf	24 lbf	47.7	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
RW155zz	52100 Chrome Steel	0.15625"	0.3125"	0.125"	0.221"	0.1562"	Shielded	69 lbf	27 lbf	53	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SRW155	440C Stainless Steel	0.15625"	0.3125"	0.1094"	0.221"	0.1406"	Open	62 lbf	24 lbf	47.7	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant

Inch Extended

RW155	52100 Chrome Steel	0.15625"	0.3125"	0.1094"	0.221"	0.1406"	Open	69 lbf	27 lbf	53	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SRW2zz	440C Stainless Steel	0.125"	0.375"	0.1562"	0.2"	0.1875"	Shielded	109 lbf	35 lbf	50.4	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
RW2-6zz	52100 Chrome Steel	0.125"	0.375"	0.1406"	0.173"	0.1719"	Shielded	122 lbf	41 lbf	53	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
RW2zz	52100 Chrome Steel	0.125"	0.375"	0.1562"	0.2"	0.1875"	Shielded	121 lbf	39 lbf	56	Inch	Ball	Extended	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant