

SSUCPA SERIES



Product Number	Shaft Size	H	L	J	Basic Load Ratings Cr	Basic Load Ratings Cor	Material	Precision	ISO 9001	Rohs	Clearance
Ssucpa207 21	SSPA207	SSUC207-21	1-5/16 in	47.6 mm 1-7/8 in	110 mm 4-11/32 in	80 mm 3-5/32 in	21.8 kN 4901 lbf	12.3 kN 2765 lbf	Stainless	P0	YES
Ssucpa207 20	SSPA207	SSUC207-20	1-1/4 in	47.6 mm 1-7/8 in	110 mm 4-11/32 in	80 mm 3-5/32 in	21.8 kN 4901 lbf	12.3 kN 2765 lbf	Stainless	P0	YES
Ssucpa206 20	SSPA206	SSUC206-20	1-1/4 in	42.9 mm 1-11/16 in	94 mm 3-11/16 in	66 mm 2-19/32 in	16.5 kN 3709 lbf	9.05 kN 2035 lbf	Stainless	P0	YES
Ssucpa206 19	SSPA206	SSUC206-19	1-3/16 in	42.9 mm 1-11/16 in	94 mm 3-11/16 in	66 mm 2-19/32 in	16.5 kN 3709 lbf	9.05 kN 2035 lbf	Stainless	P0	YES
Ssucpa206	SSPA206	SSUC206	30 mm	42.9 mm 1-11/16 in	94 mm 3-11/16 in	66 mm 2-19/32 in	16.5 kN 3709 lbf	9.05 kN 2035 lbf	Stainless	P0	YES
Ssucpa206 18	SSPA206	SSUC206-18	1-1/8 in	42.9 mm 1-11/16 in	94 mm 3-11/16 in	66 mm 2-19/32 in	16.5 kN 3709 lbf	9.05 kN 2035 lbf	Stainless	P0	YES
Ssucpa206 17	SSPA206	SSUC206-17	1-1/16 in	42.9 mm 1-11/16 in	94 mm 3-11/16 in	66 mm 2-19/32 in	16.5 kN 3709 lbf	9.05 kN 2035 lbf	Stainless	P0	YES
Ssucpa205 16	SSPA205	SSUC205-16	1 in	36.5 mm 1-7/16 in	84 mm 3-5/16 in	56 mm 2-13/64 in	11.9 kN 2675 lbf	6.3 kN 1416 lbf	Stainless	P0	YES
Ssucpa205	SSPA205	SSUC205	25 mm	36.5 mm 1-7/16 in	84 mm 3-5/16 in	56 mm 2-13/64 in	11.9 kN 2675 lbf	6.3 kN 1416 lbf	Stainless	P0	YES
Ssucpa205 15	SSPA205	SSUC205-15	15/16 in	36.5 mm 1-7/16 in	84 mm 3-5/16 in	56 mm 2-13/64 in	11.9 kN 2675 lbf	6.3 kN 1416 lbf	Stainless	P0	YES

SSUCPA SERIES

Ssucpa205 14	SSPA205	SSUC205-14	7/8 in	36.5 mm 1-7/16 in	84 mm 3-5/16 in	56 mm 2-13/64 in	11.9 kN 2675 lbf	6.3 kN 1416 lbf	Stainless	P0	YES
Ssucpa205 13	SSPA205	SSUC205-13	13/16 in	36.5 mm 1-7/16 in	84 mm 3-5/16 in	56 mm 2-13/64 in	11.9 kN 2675 lbf	6.3 kN 1416 lbf	Stainless	P0	YES
Ssucpa204	SSPA204	SSUC204	20 mm	30.2 mm 1-3/16 in	76 mm 3 in	52 mm 2-3/64 in	10.9 kN 2450 lbf	5.35 kN 1203 lbf	Stainless	P0	YES
Ssucpa204 12	SSPA204	SSUC204-12	3/4 in	30.2 mm 1-3/16 in	76 mm 3 in	52 mm 2-3/64 in	10.9 kN 2450 lbf	5.35 kN 1203 lbf	Stainless	P0	YES
Ssucpa203 11	SSPA203	SSUC203-11	11/16 in	30.2 mm 1-3/16 in	76 mm 3 in	52 mm 2-3/64 in	8.15 kN 1832 lbf	3.85 kN 866 lbf	Stainless	P0	YES
Ssucpa203	SSPA203	SSUC203	17 mm	30.2 mm 1-3/16 in	76 mm 3 in	52 mm 2-3/64 in	8.15 kN 1832 lbf	3.85 kN 866 lbf	Stainless	P0	YES
Ssucpa202 10	SSPA202	SSUC202-10	5/8 in	30.2 mm 1-3/16 in	76 mm 3 in	52 mm 2-3/64 in	8.15 kN 1832 lbf	3.85 kN 866 lbf	Stainless	P0	YES
Ssucpa202	SSPA202	SSUC202	15 mm	30.2 mm 1-3/16 in	76 mm 3 in	52 mm 2-3/64 in	8.15 kN 1832 lbf	3.85 kN 866 lbf	Stainless	P0	YES
Ssucpa202 9	SSPA202	SSUC202-9	9/16 in	30.2 mm 1-3/16 in	76 mm 3 in	52 mm 2-3/64 in	8.15 kN 1832 lbf	3.85 kN 866 lbf	Stainless	P0	YES
Ssucpa201 8	SSPA201	SSUC201-8	1/2 in	30.2 mm 1-3/16 in	76 mm 3 in	52 mm 2-3/64 in	8.15 kN 1832 lbf	3.85 kN 866 lbf	Stainless	P0	YES
Ssucpa201	SSPA201	SSUC201	12 mm	30.2 mm 1-3/16 in	76 mm 3 in	52 mm 2-3/64 in	8.15 kN 1832 lbf	3.85 kN 866 lbf	Stainless	P0	YES
Ssucpa207 22	SSPA207	SSUC207-22	1-3/8 in	47.6 mm 1-7/8 in	110 mm 4-11/32 in	80 mm 3-5/32 in	21.8 kN 4901 lbf	12.3 kN 2765 lbf	Stainless	P0	YES
Ssucpa207	SSPA207	SSUC207	35 mm	47.6 mm 1-7/8 in	110 mm 4-11/32 in	80 mm 3-5/32 in	21.8 kN 4901 lbf	12.3 kN 2765 lbf	Stainless	P0	YES
Ssucpa207 23	SSPA207	SSUC207-23	1-7/16 in	47.6 mm 1-7/8 in	110 mm 4-11/32 in	80 mm 3-5/32 in	21.8 kN 4901 lbf	12.3 kN 2765 lbf	Stainless	P0	YES
Ssucpa208 24	SSPA208	SSUC208-24	1-1/2 in	49.2 mm 1-15/16 in	116 mm 4-9/16 in	84 mm 3-5/16 in	24.8 kN 5575 lbf	14.3 kN 3215 lbf	Stainless	P0	YES

SSUCPA SERIES

Ssucpa208 25	SSPA208	SSUC208-25	1-9/16 in	49.2 mm 1-15/16 in	116 mm 4-9/16 in	84 mm 3-5/16 in	24.8 kN 5575 lbf	14.3 kN 3215 lbf	Stainless	P0	YES
Ssucpa208	SSPA208	SSUC208	40 mm	49.2 mm 1-15/16 in	116 mm 4-9/16 in	84 mm 3-5/16 in	24.8 kN 5575 lbf	14.3 kN 3215 lbf	Stainless	P0	YES