

SSUC SERIES



Part Number	Shaft Size	D	B	C	Basic Load Ratings Cr	Basic Load Ratings Cor	Material	Precision	ISO 9001	Rohs	Clearance
Ssuc212 39	2-7/16 in	110.0 mm 4.331 in	65.1 mm 2.563 in	27.0 mm 1.063 in	52.4 kN 115.5 lb	36.2 kN 79.8 lb	Stainless Steel	P0	YES	YES	Standard
Ssuc212 38	2-3/8 in	110.0 mm 4.331 in	65.1 mm 2.563 in	27.0 mm 1.063 in	52.4 kN 115.5 lb	36.2 kN 79.8 lb	Stainless Steel	P0	YES	YES	Standard
Ssuc212	60 mm	110.0 mm 4.331 in	65.1 mm 2.563 in	27.0 mm 1.063 in	52.4 kN 115.5 lb	36.2 kN 79.8 lb	Stainless Steel	P0	YES	YES	Standard
Ssuc212 36	2-1/4 in	110.0 mm 4.331 in	65.1 mm 2.563 in	27.0 mm 1.063 in	52.4 kN 115.5 lb	36.2 kN 79.8 lb	Stainless Steel	P0	YES	YES	Standard
Ssuc211 35	2-3/16 in	100.0 mm 3.937 in	55.6 mm 2.189 in	25.0 mm 0.984 in	43.4 kN 95.7 lb	29.4 kN 64.8 lb	Stainless Steel	P0	YES	YES	Standard
Ssuc211	55 mm	100.0 mm 3.937 in	55.6 mm 2.189 in	25.0 mm 0.984 in	43.4 kN 95.7 lb	29.4 kN 64.8 lb	Stainless Steel	P0	YES	YES	Standard
Ssuc211 34	2-1/8 in	100.0 mm 3.937 in	55.6 mm 2.189 in	25.0 mm 0.984 in	43.4 kN 95.7 lb	29.4 kN 64.8 lb	Stainless Steel	P0	YES	YES	Standard
Ssuc211 32	2 in	100.0 mm 3.937 in	55.6 mm 2.189 in	25.0 mm 0.984 in	43.4 kN 95.7 lb	29.4 kN 64.8 lb	Stainless Steel	P0	YES	YES	Standard
Ssuc210 32	2 in	90.0 mm 3.543 in	51.6 mm 2.031 in	24.0 mm 0.945 in	35.1 kN 77.4 lb	23.3 kN 51.4 lb	Stainless Steel	P0	YES	YES	Standard

SSUC SERIES

Ssuc210	50 mm	90.0 mm 3.543 in	51.6 mm 2.031 in	24.0 mm 0.945 in	35.1 kN 77.4 lb	23.3 kN 51.4 lb	Stainless Steel	P0	YES	YES	Standard
Ssuc210 31	1-15/16 in	90.0 mm 3.543 in	51.6 mm 2.031 in	24.0 mm 0.945 in	35.1 kN 77.4 lb	23.3 kN 51.4 lb	Stainless Steel	P0	YES	YES	Standard
Ssuc210 30	1-7/8 in	90.0 mm 3.543 in	51.6 mm 2.031 in	24.0 mm 0.945 in	35.1 kN 77.4 lb	23.3 kN 51.4 lb	Stainless Steel	P0	YES	YES	Standard
Ssuc209	45 mm	85.0 mm 3.346 in	49.2 mm 1.937 in	22.0 mm 0.866 in	34.1 kN 75.2 lb	21.3 kN 47 lb	Stainless Steel	P0	YES	YES	Standard
Ssuc209 28	1-3/4 in	85.0 mm 3.346 in	49.2 mm 1.937 in	22.0 mm 0.866 in	34.1 kN 75.2 lb	21.3 kN 47 lb	Stainless Steel	P0	YES	YES	Standard
Ssuc209 27	1-11/16 in	85.0 mm 3.346 in	49.2 mm 1.937 in	22.0 mm 0.866 in	34.1 kN 75.2 lb	21.3 kN 47 lb	Stainless Steel	P0	YES	YES	Standard
Ssuc209 26	1-5/8 in	85.0 mm 3.346 in	49.2 mm 1.937 in	22.0 mm 0.866 in	34.1 kN 75.2 lb	21.3 kN 47 lb	Stainless Steel	P0	YES	YES	Standard
Ssuc208	40 mm	80.0 mm 3.150 in	49.2 mm 1.937 in	21.0 mm 0.827 in	29.1 kN 64.2 lb	17.8 kN 39.2 lb	Stainless Steel	P0	YES	YES	Standard
Ssuc208 25	1-9/16 in	80.0 mm 3.150 in	49.2 mm 1.937 in	21.0 mm 0.827 in	29.1 kN 64.2 lb	17.8 kN 39.2 lb	Stainless Steel	P0	YES	YES	Standard
Ssuc208 24	1-1/2 in	80.0 mm 3.150 in	49.2 mm 1.937 in	21.0 mm 0.827 in	29.1 kN 64.2 lb	17.8 kN 39.2 lb	Stainless Steel	P0	YES	YES	Standard
Ssuc207 23	1-7/16 in	72.0 mm 2.835 in	42.9 mm 1.689 in	20.0 mm 0.787 in	25.7 kN 56.7 lb	15.4 kN 34 lb	Stainless Steel	P0	YES	YES	Standard
Ssuc207	35 mm	72.0 mm 2.835 in	42.9 mm 1.689 in	20.0 mm 0.787 in	25.7 kN 56.7 lb	15.4 kN 34 lb	Stainless Steel	P0	YES	YES	Standard
Ssuc207 22	1-3/8 in	72.0 mm 2.835 in	42.9 mm 1.689 in	20.0 mm 0.787 in	25.7 kN 56.7 lb	15.4 kN 34 lb	Stainless Steel	P0	YES	YES	Standard

SSUC SERIES

Ssuc207 21	1-5/16 in	72.0 mm 2.835 in	42.9 mm 1.689 in	20.0 mm 0.787 in	25.7 kN 56.7 lb	15.4 kN 34 lb	Stainless Steel	P0	YES	YES	Standard
Ssuc207 20	1-1/4 in	72.0 mm 2.835 in	42.9 mm 1.689 in	20.0 mm 0.787 in	25.7 kN 56.7 lb	15.4 kN 34 lb	Stainless Steel	P0	YES	YES	Standard
Ssuc206 20	1-1/4 in	62.0 mm 2.441 in	38.1 mm 1.500 in	19.0 mm 0.748 in	19.5 kN 43 lb	11.3 kN 24.9 lb	Stainless Steel	P0	YES	YES	Standard
Ssuc206 19	1-3/16 in	62.0 mm 2.441 in	38.1 mm 1.500 in	19.0 mm 0.748 in	19.5 kN 43 lb	11.3 kN 24.9 lb	Stainless Steel	P0	YES	YES	Standard
Ssuc206	30 mm	62.0 mm 2.441 in	38.1 mm 1.500 in	19.0 mm 0.748 in	19.5 kN 43 lb	11.3 kN 24.9 lb	Stainless Steel	P0	YES	YES	Standard
Ssuc206 18	1-1/8 in	62.0 mm 2.441 in	38.1 mm 1.500 in	19.0 mm 0.748 in	19.5 kN 43 lb	11.3 kN 24.9 lb	Stainless Steel	P0	YES	YES	Standard
Ssuc205 16	1 in	52.0 mm 2.047 in	34.1 mm 1.343 in	17.0 mm 0.669 in	14.0 kN 30.9 lb	7.85 kN 17.3 lb	Stainless Steel	P0	YES	YES	Standard
Ssuc205	25 mm	52.0 mm 2.047 in	34.1 mm 1.343 in	17.0 mm 0.669 in	14.0 kN 30.9 lb	7.85 kN 17.3 lb	Stainless Steel	P0	YES	YES	Standard