

SGE..ET-2RS SERIES



Part Number	Radial Static Limit Load Capacity	B Ball Bore Max	D Outside Diameter Max	W Ball Width Max	H Rac Width Max	System of Measurement	Material	Temperature Range	RoHS	ISO: 9001	Radial Clearance
Sge35et 2rs	224 kN	35.000 mm	55.000 mm	25.00 mm	20.00 mm	Metric	Steel	-50° to 120° C	Compliant	Compliant	Standard
Sge30et 2rs	176 kN	30.000 mm	47.000 mm	22.00 mm	18.00 mm	Metric	Steel	-50° to 120° C	Compliant	Compliant	Standard
Sge25et 2rs	137 kN	25.000 mm	42.000 mm	20.00 mm	16.00 mm	Metric	Steel	-50° to 120° C	Compliant	Compliant	Standard
Sge20et 2rs	83 kN	20.000 mm	35.000 mm	16.00 mm	12.00 mm	Metric	Steel	-50° to 120° C	Compliant	Compliant	Standard
Sge17et 2rs	60 kN	17.000 mm	30.000 mm	14.00 mm	10.00 mm	Metric	Steel	-50° to 120° C	Compliant	Compliant	Standard
Sge15et 2rs	47 kN	15.000 mm	26.000 mm	12.00 mm	9.00 mm	Metric	Steel	-50° to 120° C	Compliant	Compliant	Standard
Sge40et 2rs	280 kN	40.000 mm	62.000 mm	28.00 mm	22.00 mm	Metric	Steel	-50° to 120° C	Compliant	Compliant	Standard
Sge45et 2rs	360 kN	45.000 mm	68.000 mm	32.00 mm	25.00 mm	Metric	Steel	-50° to 120° C	Compliant	Compliant	Standard
Sge50et 2rs	440 kN	50.000 mm	75.000 mm	35.00 mm	28.00 mm	Metric	Steel	-50° to 120° C	Compliant	Compliant	Standard
Sge60et 2rs	695 kN	60.000 mm	90.000 mm	44.00 mm	36.00 mm	Metric	Steel	-50° to 120° C	Compliant	Compliant	Standard