

NSSB NSSB-V SERIES



Part Number	Ball Flat Diameter	Ball Diameter REF	Misalign Angle	B Ball Bore	D Outside Diameter	W Ball Width	T Race Width	E V Groove Diameter	System of Measurement	Material	Temperature Range	RoHS	ISO: 9001	Radial Clearance
NSSB-8V	0.641	0.8129	8	0.5	1	0.5	0.39	0.878	Inch	Steel	-20°to80°C	Compliant	Compliant	Standard
NSSB-7V	0.57	0.718	8	0.4375	0.9062	0.437	0.343	0.81	Inch	Steel	-20°to80°C	Compliant	Compliant	Standard
NSSB-6V	0.515	0.656	9	0.375	0.8125	0.406	0.312	0.714	Inch	Steel	-20°to80°C	Compliant	Compliant	Standard
NSSB-5V	0.419	0.56	10	0.3125	0.75	0.375	0.281	0.652	Inch	Steel	-20°to80°C	Compliant	Compliant	Standard
NSSB-3V	0.293	0.406	10	0.19	0.5625	0.281	0.218	0.502	Inch	Steel	-20°to80°C	Compliant	Compliant	Standard
NSSB-4V	0.364	0.5	10	0.25	0.6562	0.343	0.25	0.596	Inch	Steel	-20°to80°C	Compliant	Compliant	Standard
NSSB-14V	0.978	1.312	8	0.875	1.5625	0.875	0.703	1.44	Inch	Steel	-20°to80°C	Compliant	Compliant	Standard
NSSB-12V	0.92	1.187	8	0.75	1.4375	0.75	0.593	1.315	Inch	Steel	-20°to80°C	Compliant	Compliant	Standard
NSSB-16V	1.118	1.5	9	1	1.75	1	0.797	1.628	Inch	Steel	-20°to80°C	Compliant	Compliant	Standard
NSSB-10V	0.739	0.968	8	0.625	1.1875	0.625	0.5	1.065	Inch	Steel	-20°to80°C	Compliant	Compliant	Standard