

WSSB WSSB-V SERIES



Part Number	Ball Flat Diameter	Ball Diameter REF	Misalign Angle	B Ball Bore	D Outside Diameters	W Ball Width	T Race Width	E V Groove Diameter	System of Measurement	Material	Temperature Range	RoHS	ISO: 9001	Radial Clearance
WSSB-4V	0.301	0.531	15	0.25	0.625	0.437	0.327	0.564	Inch	Steel	-20° to 80° C	Compliant	Compliant	Standard
WSSB-3V	0.301	0.531	15	0.19	0.625	0.437	0.327	0.564	Inch	Steel	-20° to 80° C	Compliant	Compliant	Standard
WSSB-16V	1.275	1.875	12	1	2.125	1.375	1.005	2.003	Inch	Steel	-20° to 80° C	Compliant	Compliant	Standard
WSSB-14V	1.061	1.375	6	0.875	1.625	0.875	0.755	1.503	Inch	Steel	-20° to 80° C	Compliant	Compliant	Standard
WSSB-12V	0.892	1.25	13	0.75	1.375	0.875	0.63	1.253	Inch	Steel	-20° to 80° C	Compliant	Compliant	Standard
WSSB-10V	0.752	1.062	12	0.625	1.1875	0.75	0.567	1.089	Inch	Steel	-20° to 80° C	Compliant	Compliant	Standard
WSSB-5V	0.401	0.593	14	0.3125	0.6875	0.437	0.317	0.627	Inch	Steel	-20° to 80° C	Compliant	Compliant	Standard
WSSB-6V	0.471	0.687	8	0.375	0.8125	0.5	0.406	0.714	Inch	Steel	-20° to 80° C	Compliant	Compliant	Standard
WSSB-7V	0.542	0.781	10	0.4375	0.9375	0.562	0.442	0.839	Inch	Steel	-20° to 80° C	Compliant	Compliant	Standard
WSSB-8V	0.612	0.875	9	0.5	1	0.625	0.505	0.902	Inch	Steel	-20° to 80° C	Compliant	Compliant	Standard